



TERMOVENTILATED PELLET STOVE



YURA		14	18	22	26	30
ENERGY CLASS		A+	A+	A+	A+	A+
DIMENSIONS (L x D x H)	cm	46x48x95	55x59x111	59x68x122	70x74x137	70x74x137
WEIGHT	kg	145	160	230	280	280
NOMINAL INPUT (min.-max.)	kW	5,23 - 14,79	4,1 - 18	5,26 - 23,12	8,95 - 27,34	8,95 - 32,41
NOMINAL OUTPUT (min.-max.)	kW	5,04 - 13,84	4 - 17,14	5,08 - 21,96	8,57 - 25,86	8,57 - 30,48
OUTPUT TO THE WATER (min.-max.)	kW	3,81 - 10,53	3,10 - 13,43	4,20 - 17,86	6,51 - 20,35	6,51 - 24,38
OUTPUT TO THE ROOM (min.-max.)	kW	1,22 - 3,31	0,9 - 3,7	0,88 - 4,10	2,06 - 5,51	2,06 - 6,1
EXCHANGER WATER CONTENT	l	17	31	50	60	60
EXPANSION VESSEL CAPACITY	l	6	7	8	8	8
MAXIMUM WORKING PRESSURE	bar	3	3	3	3	3
MANOMETRIC HEAD OF THE PUMP	m	6	6	6	6	6
WATER SIDE PRESSURE DROP ( $\Delta t$ 10 K) / ( $\Delta t$ 20 K)	mbar	-	181 / 45,2	186,8 / 46,7	285,9 / 71,5	405 / 101,2
EFFICIENCY % (min.-max.)	%	93,54 - 96,29	97,54 - 94,97	95,74 - 96,71	95,79 - 94,56	95,79 - 94,03
MINIMUM DRAUGHT AT THE CHIMNEY BASE	Pa	12	8	10	6	6
SMOKE OUTLET	mm $\varnothing$	80	80	80	100	100
AIR DUCT DIAMETER	mm $\varnothing$	50	50	50	50	50
PELLET RESERVOIR CONTENT	kg	17	33	38	57	57
AVERAGE CONSUMPTION (min.-max.)	kg/h	1,067 - 3,017	0,84 - 3,7	1,113 - 4,893	1,8 - 5,5	1,8 - 6,3
ELECTRIC ABSORPTION (nominal / at ignition stage)	W	82 - 350	82 - 350	145 - 400	165 - 430	165 - 430
HEATING VOLUME	m <sup>3</sup>	340	420	510	600	730
NOISINESS	dB	35 / 45	35 / 50	35 / 50	35 / 50	35 / 50

PRODUCT PLUS VALUES



HYDRO VENTILATED



HYDRO (mod. 14)



STEEL BRAZIER (mod. 14)



CAST IRON BRAZIER



MAGIC GLASS



REAR SMOKE OUTLET



POWER MODULATION



WEEKLY PROGRAMMING



DISPLAY



WI-FI (optional)



Black



White



Burgundy

