



T-PET BOILER

T-PET BOILER

CALDAIA A PELLETT



T-PET BOILER		14	18	22	26	30
CLASSE ENERGETICA		A+	A+	A+	A+	A+
DIMENSIONI (LxPxH)	cm	56,2x70x108	63x78,7x125	63x78,7x125	69x76,4x136	69x76,4x136
PESO STUFA	kg	150	240	240	305	305
POTENZA TERMICA INTRODotta (min.-max)	kW	4,5 - 15,1	5,86 - 19	6,8 - 23	7 - 27,1	7 - 31,5
POTENZA TERMICA NOMINALE (min.-max)	kW	4,1 - 13,8	5,21 - 17,51	6,3 - 21	6,3 - 25	6,34 - 29
POTENZA RESA ALL'ACQUA (min.-max)	kW	4,1 - 13,8	5,21 - 17,51	6,3 - 21	6,3 - 25	6,34 - 29
CONTENUTO FLUIDO SCAMBIATORE	l	31	50	50	60	60
VASO ESPANSIONE	l	7	8	8	8	8
PRESSIONE D'ESERCIZIO MASSIMA	bar	3	3	3	3	3
PREVALENZA DELLA POMPA	m	6	6	6	6	6
RESISTENZA LATO ACQUA (Δt 10 K) / (Δt 20 K)	mbar	181 / 45,2	123,5 / 30,9	123,5 / 30,9	285,9 / 71,5	405 / 101,2
RENDIMENTO POTENZA % (min.-max)	%	90,6 - 91,2	88,82 - 92,13	92,1 - 91,1	90,65 - 92,2	90,65 - 92,1
TIRAGGIO MINIMO CAMINO	Pa	12	10	10	9	10
DIAMETRO SCARICO FUMI	mm \emptyset	80	80	80	100	100
DIAMETRO CONDOTTO ASPIRAZIONE	mm \emptyset	50	50	50	60	60
CAPACITÀ SERBATOIO	kg	46	60	60	81	81
CONSUMO PELLETT min.-max	kg/h	0,91 - 3,14	1,195 - 3,875	1,31 - 3,96	1,43 - 5,5	1,43 - 6,5
ASSORBIMENTO ELETTRICO nom./acc.	W	74 - 330	67 - 330	76 - 330	85 - 330	95 - 330
VOLUME RISCALDABILE	m ³	450	470	540	630	630
RUMOROSITÀ	dB	35 / 50	35 / 50	35 / 50	35 / 50	35 / 50

PLUS PRODOTTO



CALDAIA SOLO RISCALDAMEN.



BRACIERE IN GHISA



MODULAZ. DI POTENZA



USCITA FUMI POSTERIORE



PROGRAMMAZ. SETTIMANALE



DISPLAY



WI-FI (optional)



mod. 14



mod. 18-22



mod. 26-30

