



T-PET BOILER

T-PET BOILER

CALDAIA A PELLETT



T-PET BOILER		14	18	22	26	30
CLASSE ENERGETICA		A+	A+	A+	A+	A+
DIMENSIONI (LxPxH)	cm	56,2x70x108	63x78,7x125	63x78,7x125	69x76,4x136	69x76,4x136
PESO STUFA	kg	150	240	240	305	305
POTENZA TERMICA INTRODotta (min.-max)	kW	4,5 - 15,1	5,86 - 19	6,8 - 23	7 - 27,1	7 - 31,5
POTENZA TERMICA NOMINALE (min.-max)	kW	4,1 - 13,8	5,21 - 17,51	6,3 - 21	6,3 - 25	6,34 - 29
POTENZA RESA ALL'ACQUA (min.-max)	kW	4,1 - 13,8	5,21 - 17,51	6,3 - 21	6,3 - 25	6,34 - 29
CONTENUTO FLUIDO SCAMBIATORE	l	31	50	50	60	60
VASO ESPANSIONE	l	7	8	8	8	8
PRESSIONE D'ESERCIZIO MASSIMA	bar	3	3	3	3	3
PREVALENZA DELLA POMPA	m	6	6	6	6	6
RESISTENZA LATO ACQUA (Δt 10 K) / (Δt 20 K)	mbar	181 / 45,2	123,5 / 30,9	123,5 / 30,9	285,9 / 71,5	405 / 101,2
RENDIMENTO POTENZA % (min.-max)	%	90,6 - 91,2	88,82 - 92,13	92,1 - 91,1	90,65 - 92,2	90,65 - 92,1
TIRAGGIO MINIMO CAMINO	Pa	12	10	10	9	10
DIAMETRO SCARICO FUMI	mm Ø	80	80	80	100	100
DIAMETRO CONDOTTO ASPIRAZIONE	mm Ø	50	50	50	60	60
CAPACITÀ SERBATOIO	kg	46	60	60	81	81
CONSUMO PELLETT min.-max	kg/h	0,91 - 3,14	1,195 - 3,875	1,31 - 3,96	1,43 - 5,5	1,43 - 6,5
ASSORBIMENTO ELETTRICO nom./acc.	W	74 - 330	67 - 330	76 - 330	85 - 330	95 - 330
VOLUME RISCALDABILE	m³	450	470	540	630	630
RUMOROSITÀ	dB	35 / 50	35 / 50	35 / 50	35 / 50	35 / 50

PLUS PRODOTTO



**CALDAIA
SOLO
RISCALDAMEN.**



**BRACIERE
IN GHISA**



**MODULAZ.
DI POTENZA**



**USCITA FUMI
POSTERIORE**



**PROGRAMMAZ.
SETTIMANALE**



DISPLAY



**WI-FI
(optional)**



mod. 14



mod. 18-22



mod. 26-30

